

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 November 2002 (14.11.2002)

PCT

(10) International Publication Number
WO 02/090699 A1

(51) International Patent Classification⁷: **E05F 5/10**, 15/16

(21) International Application Number: PCT/GB02/02095

(22) International Filing Date: 7 May 2002 (07.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0111252.3 9 May 2001 (09.05.2001) GB

(71) Applicant and

(72) Inventor: GUNTON, Bruce, Stanley [GB/GB]; 3 Gisborne Close, Yoxall, Staffordshire DE13 8NU (GB).

(74) Agent: SKINNER, Michael; Swindell & Pearson, 48 Friar Gate, Derby DE1 1GY (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DRIVE ARRANGEMENT



(57) Abstract: A drive arrangement (10) for a shaft (12), such as a shaft for driving a sectional door, roller shutter or the like, is in the form of a module, carried, in use, by the shaft (12) and including a motor (14), a driven wheel (16) fixed for rotation with the shaft (12) and drivable, in use, by the motor (14), and clutch means (18) and operable between the motor (14) and the wheel (16). The module further includes brace means (20) in the form of a limb attachable to a member which is fixed relative to the axis of the shaft (12), to brace the module against turning as the shaft (12) is driven.



WO 02/090699 A1

Drive Arrangement

The present invention relates to drive arrangements and in particular, but not exclusively, to drive arrangements for driving shafts of electrically operated doors, shutters and the like.

Many doors, such as up-and-over garage doors, roller shutter doors and the like are provided with motors for driving the doors to open or close. In previous proposals, the motor may be mounted on a framework or door surround but previous proposals have proved bulky or difficult and time consuming to fit, particularly when fitted to existing door systems in place of other motor arrangements.

The present invention provides a drive arrangement for a shaft, the arrangement having a module which is carried, in use, by the shaft and includes a motor, a driven wheel fixed, in use, for rotation with the shaft and drivable, in use, by the motor, and clutch means operable between the motor and the wheel, the module further comprising brace means attachable to a member which is fixed relative to the shaft axis, to brace the module against turning as the shaft is driven.

The driven wheel is preferably fitted around the shaft and keyed thereto.

The module may comprise a base assembly, and a bearing assembly by which the driven wheel is mounted on the base assembly, whereby the module is carried by the shaft by means of the driven wheel being fixed for rotation with the shaft.

Preferably the motor drives a drive wheel, and the module has a belt around the drive wheel and the driven wheel. The clutch means preferably serves to movably mount the motor and drive wheel relative to the driven wheel, so that the belt can be releasably engaged with the wheels by means of relative movement between the wheels. The module may have a base assembly

carried by the shaft, and a carriage assembly carried by the base assembly and movable relative thereto. The base assembly may have a first member fixed relative to the rotation axis of the driven wheel, the carriage assembly having a second member fixed relative to the rotation axis of the drive wheel, the first and second members being movable relative to one another. The first and second members may be plate members.

The module may include pillar members fixed relative to the first or second member, and slots formed in the second or first member, respectively, to allow relative movement of the first and second members.

The arrangement may further comprise a clutch actuating means by which the clutch may be engaged and disengaged. The actuating means may include a cable. The actuating means may include tension means operable, in use, to apply releasable tension to the cable, to cause the cable to pull the clutch means to the engaged condition. The actuating means may include an over-centre catch mechanism. The actuating means may be mounted at a position which is fixed relative to the axis of the shaft.

The brace means may be a limb carried by the module and extending to a distal end at which the limb may be attached to a fixed member, as aforesaid.

One embodiment of the invention will now be described in more detail, by way of example only, and with reference to the accompanying drawings, in which:-

Fig. 1 is a front perspective view of an embodiment of the present invention installed for driving a shaft;

Fig. 2 is a rear perspective view of the arrangement of Fig. 1;

Fig. 3 is a front elevation of the arrangement of Figs. 1 and 2;

Fig. 4 is an end elevation of the arrangement; and

Fig. 5 is a section of the arrangement, along the line V-V of Fig. 3.

Fig. 1 shows a drive arrangement 10 for a shaft 12, such as a shaft for driving a sectional door, roller shutter or the like. The arrangement 10 is in the

form of a module, carried, in use, by the shaft 12 and including a motor 14, a driven wheel 16 fixed for rotation with the shaft 12 and drivable, in use, by the motor 14, and clutch means indicated generally at 18 and operable between the motor 14 and the wheel 16. The module further includes brace means 20 (Fig. 2) in the form of a limb attachable to a member which is fixed relative to the axis of the shaft 12, to brace the module against turning as the shaft 12 is driven.

In more detail, the module 10 has a back plate 22 attached by means of two upper pillars 24 and a lower pillar 26 to a front plate 28. The driven wheel 16 is located between the plates 22, 28 and mounted to them by bearings 30 (Fig. 5). The wheel 16 is fitted around the shaft 12. The shaft 12 and wheel 16 both have corresponding keyways to allow the introduction of a loose key 32 into both keyways, so that the wheel 16 is fixed for rotation with the shaft 12. Drive to the wheel 16 is provided through a belt 34 from a drive wheel 36. The drive wheel 36 is driven by the motor 14 through a gearbox 38 which has an output shaft 40 on which the wheel 36 is mounted.

Consequently, operation of the motor 14 acts, through the gearbox 38 to turn the shaft 40 and thus the wheel 36. If the belt 34 is engaged with the wheel 36 and also with the wheel 16, this drive is passed to the wheel 16 and thus to the shaft 12, thereby driving the door, shutter etc. However, the engagement of the belt 34 with the wheels 16, 36 is releasable, as can now be described.

In addition to the back and front plates 22, 28, which are fixed in position relative to the rotation axis of the shaft 12, the arrangement 10 further includes a slider plate 42 which carries the gearbox 38. The motor 14 may be mounted directly on the slider plate 42, or on the gearbox 38. However, the motor 14 and gearbox 38, and thus the output shaft 40 and drive wheel 36 are fixed to the slider plate 42.

The slider plate 42 has upper slots 44 to receive the upper pillars 24, and a lower slot 46 to receive the lower pillar 26. The fit of the pillars 24, 26 in the

slots 44, 46 allows the plate 42 to slide to a limited extent, relative to the plates 22, 28. A further slot 48 may be provided in the back plate 22 to receive the free end of the output shaft 40. The slider plate 42 thus forms a carriage by which the motor 14 and gearbox 38 move relative to the back plate 22 and front plate 28.

In consequence, the separation of the rotation axis of the wheels 16, 36 can be changed by sliding the plate 42 relative to the plates 22, 28. If the wheel 36 is moved away from the wheel 16, the belt 34 will tend to tighten until the belt 34 is driven by the wheel 36, and conveys the drive to the wheel 16. However, if the wheel 36 is moved towards the wheel 16, or is released to be free to move, engagement between the belt 34 and the wheels 16, 36 will be lost, and drive will not be conveyed as just described. The sliding motion of the plate 42 thus provides the arrangement 10 with a form of clutch between the motor 14 and the wheel 16.

In normal use, it is envisaged that the clutch will remain engaged, with the belt 24 engaging the wheels 16, 36. To this end, a clutch cable 50 is secured at one end to the plate 42 and provided, at its other end, with an arrangement (not shown) for pulling the cable 50 in order to pull the wheel 36 away from the wheel 16 and tighten the belt 34. The pulling arrangement may be an over-centre catch mechanism mounted at a convenient position, such as on the door frame or adjacent wall. It is envisaged that the cable 50 would be continuously pulled in this manner, during normal use, so that the belt 34 and wheels 16, 36 are normally engaged. Rotation of the shaft 12 (including the direction of rotation) can therefore be controlled by appropriate control of the motor 14. However, in the event that motor control is to be overridden (such as in the case of an emergency, fault in the motor or drive, or obstruction of the door being driven), tension on the cable 50 would be released, allowing the plate 42 to move up, releasing the engagement between the belt 34 and the wheels 16, 36.

In addition to the cable 50, the drawings show an alternative override mechanism which includes an over-centre catch 52 mounted on the front plate 28, and a claw 54 reaching above the front plate 28 and over the edge of the

slider plate 42. When the catch 52 is engaged as shown in Fig. 1, the claw 54 pulls the plate 42 down, to engage the belt 34 with the wheels 16, 36, as has been described. Alternatively, the catch 52 can be released by pulling the tab 56 away from the plate 28, thus releasing the pull of the claw 54 on the slider plate 42 and disengaging the belt 34, as has been described. It is envisaged that the claw 54 and cable 50 would not both be provided in a single installation, because both would need to be released in order to override the motor 14, but it is convenient to illustrate both alternatives in a single drawing. It is envisaged that tension on the cable 50 may be controlled by an over-centre catch of the type illustrated at 52.

It is envisaged that the belt 34 may be a strongly resilient material such as a synthetic plastic or rubber material, preferably having a plurality of V-shaped ribs along its length, and fitting into corresponding V-shaped circumferential grooves in the wheels 16, 36, as can be seen in Fig. 5. Alternatively, a toothed belt could be used. A chain could be used with toothed wheels, but it is envisaged that more elaborate arrangements would then be required to ensure that the drive is fully disengaged by the operation of the clutch. Further alternative arrangements could be envisaged.

A fixing screw or other arrangement is preferably provided to prevent movement of the arrangement 10 axially along the shaft 12.

It will be understood from the above description and the accompanying drawings that when the motor 14 is in use, the arrangement 10 will seek to apply torque to the shaft 12 in order to move the door, shutter arrangement etc. The reaction to this torque will tend to turn the arrangement 10 about the axis of the shaft 12. This torque is borne by the limb 20. The limb 20 is a rigid arm fixed at one end to the back plate 22, and extends away to a distal end 58 at which the limb 20 carries a plate 60. The plate 60 has bolt apertures 62 by which the plate 60 can be secured to a convenient member fixed relative to the axis of the shaft 12. The arrangement is then braced against turning as the shaft 12 is driven. The limb 20 is preferably adjustable in length, to assist in readily fixing in this manner, and may be attached to the plate 22 in a manner

which readily allows for changes in the angle at which the limb 20 extends away from the back plate 22.

The arrangement described above can readily be installed for driving an existing shaft 12, in the following manner. First, the module, which is self-contained, is offered to the end of the shaft 12 to fit the wheel 16 over the shaft end, and may be secured against further axial movement, as described above. The weight of the module is then supported by the shaft 12. The limb 20 is then secured to an appropriate member, such as a part of the door surround, or a convenient nearby wall. This is the only external fixing required if the catch 52 is being used. If the cable 50 is to be used, an appropriate arrangement must be made at the other end of the cable 50. The arrangement 10 is then in condition for use, as described above.

It will therefore be understood that installation is relatively simple in comparison with many prior proposals, and in particular, can require only a single member (the plate 60) to be bolted to a fixed structure.

It will be apparent from the above description that many variations and modifications can be made to the apparatus described above, without departing from the scope of the present invention. In particular, many different materials and many different shapes, sizes and relative shapes and sizes can be used for the various components. The cable 50 could, alternatively, be a chain or other flexible elongate member able to control the clutch. The term "cable" should therefore be interpreted as extending to cover these alternatives.


Whilst endeavouring in the foregoing specification to draw attention to those features of the invention believed to be of particular importance it should be understood that the Applicant claims protection in respect of any patentable feature or combination of features hereinbefore referred to and/or shown in the drawings whether or not particular emphasis has been placed thereon.


CLAIMS

1. A drive arrangement for a shaft, the arrangement having a module which is carried, in use, by the shaft and includes a motor, a driven wheel fixed, in use, for rotation with the shaft and drivable, in use, by the motor, and clutch means operable between the motor and the wheel, the module further comprising brace means attachable to a member which is fixed relative to the shaft axis, to brace the module against turning as the shaft is driven.
2. An arrangement according to claim 1 in which the driven wheel is fitted around the shaft and keyed thereto.
3. An arrangement according to claim 1 or claim 2 in which the motor drives a drive wheel, and the module has a belt around the drive wheel and the driven wheel.
4. An arrangement according to claim 3 in which the clutch means serves to movably mount the motor and drive wheel relative to the driven wheel, so that the belt can be releasably engaged with the wheels by means of relative movement between the wheels.
5. An arrangement according to any of the preceding claims in which the module comprises a base assembly, and a bearing assembly by which the driven wheel is mounted on the base assembly, whereby the module is carried by the shaft by means of the driven wheel being fixed for rotation with the shaft.
6. An arrangement according to claim 5 in which the base assembly is carried by the shaft, and the module has a carriage assembly carried by the base assembly is movable relative thereto.
7. An arrangement according to claim 6 in which the base assembly has a first member fixed relative to the rotation axis of the driven wheel, the carriage assembly having a second member fixed relative to the rotation axis of the drive wheel, the first and second members being movable relative to one another.

8. An arrangement according to claim 7 in which the first and second members are plate members.
9. An arrangement according to claim 7 or claim 8 in which the module includes pillar members fixed relative to the first or second member, and slots formed in the second or first member, respectively, to allow relative movement of the first and second members.
10. An arrangement according to any of the preceding claims in which the arrangement further comprises a clutch actuating means by which the clutch may be engaged and disengaged.
11. An arrangement according to claim 10 in which the actuating means includes a cable.
12. An arrangement according to claim 11 in which the actuating means includes tension means operable, in use, to apply releasable tension to the cable, to cause the cable to pull the clutch means to the engaged condition.
13. An arrangement according to any of claims 10 to 12 in which the actuating means includes an over-centre catch mechanism.
14. An arrangement according to any of claims 10 to 13 in which the actuating means is mounted at a position which is fixed relative to the axis of the shaft.
15. An arrangement according to any of the preceding claims in which the brace means is a limb carried by the module and extending to a distal end at which the limb may be attached to a fixed member, as aforesaid.
16. An arrangement as substantially hereinbefore described with reference to the accompanying drawings.

17. Any novel subject matter or combination including novel subject matter disclosed herein, whether or not within the scope of or relating to the same invention as any of the preceding claims.










Fig. 3





File 5

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 02/02095

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E05F15/10 E05F15/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 E05F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 981 195 A (GUNTON BRUCE STANLEY) 23 February 2000 (2000-02-23) column 4, line 36 -column 5, line 13 figures 1-3	1-17
X	US 4 560 046 A (PLAMPER GUENTER F ET AL) 24 December 1985 (1985-12-24) column 4, line 19 - line 38 figures 7,8	1-8,10, 11,15-17
X	US 4 311 225 A (YAMAUCHI KOZI ET AL) 19 January 1982 (1982-01-19) column 9, line 32 - line 63 figure 8	1-8,10, 15-17

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

5 September 2002

Date of mailing of the international search report

13/09/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bitton, A

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/02095

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0981195	A	23-02-2000	EP 0981195 A2	23-02-2000
			GB 2342389 A	12-04-2000
			US 6188198 B1	13-02-2001
<hr/>				
US 4560046	A	24-12-1985	NONE	
<hr/>				
US 4311225	A	19-01-1982	JP 54162830 A	24-12-1979
			JP 54163269 A	25-12-1979
			JP 1347934 C	13-11-1986
			JP 54162832 A	24-12-1979
			JP 61012142 B	07-04-1986
			JP 1319855 C	29-05-1986
			JP 54163270 A	25-12-1979
			JP 60046294 B	15-10-1985
			JP 1404518 C	09-10-1987
			JP 54163271 A	25-12-1979
			JP 62007426 B	17-02-1987
			JP 1347935 C	13-11-1986
			JP 54163272 A	25-12-1979
			JP 61008306 B	13-03-1986
			JP 54163273 A	25-12-1979
			CA 1130328 A1	24-08-1982
			DE 2924015 A1	24-01-1980
<hr/>				